




## ECM-CFS

### 8th Gen Intel® Core™ i7/i5/i3/Celeron® 3.5" Micro Module with Intel® Q370 chipset



- > Intel® Coffee Lake Low power LGA 6+2, 4+2 (35W) Processor
- > Intel® Q370/H310 Express Chipset
- > One 260-pin SODIMM Socket Up to 16GB DDR4 2400/2666MHz
- > Triple Display, 2-HDMI, 18/24-bit 2-CH LVDS
- > Rich I/Os, 2-SATA III, 1-Mini PCIe, 4-USB 3.1, 2-USB 2.0, 2-COM, 2-LAN, 8-bit GPIO
- > Realtek AL892 Audio Codec
- > Dual Intel® Gigabit LAN Chipset
- > TPM 2.0 (Optional)

#### + Spec

System	
<b>Processor</b>	Intel® Core™ i7-8700T Processor (12M Cache, up to 4.00 GHz) Intel® Core™ i5-8500T Processor (9M Cache, up to 3.50 GHz) Intel® Core™ i3-8100T Processor (6M Cache, 3.10 GHz) Intel® Pentium® Gold G5400T Processor (4M Cache, 3.10 GHz) Intel® Celeron® G4900T Processor (2M Cache, 2.90 GHz)
<b>System Chipset</b>	Intel® Q370/H310 Express Chipset
<b>System Memory</b>	1 x 260-pin SODIMM Socket Up to 16GB DDR4 2400/2666MHz
<b>BIOS</b>	AMI UEFI BIOS, 256 Mbit SPI Flash ROM
<b>Watchdog Timer</b>	H/W Reset, 1sec. ~ 65535sec.
<b>H/W Status Monitor</b>	Monitoring CPU & System Temperature and Voltage
Expansion	
<b>Expansion</b>	1 x Mini PCIe (mSATA) (Q370 support Mini PCIe/mSATA device) (H310 support mSATA device)
Storage	
<b>Storage</b>	1 x mSATA
I/O	
<b>USB</b>	2 x USB 2.0 4 x USB 3.1 (Q370 support USB3.1 Gen2) (H310 support USB3.1 Gen1)
<b>SATA</b>	2 x SATA III
<b>COM Port</b>	2 x RS-232
<b>MIO</b>	1 x LPC 1 x SPI
<b>GPIO</b>	1 x 8bit GPIO
Display	
<b>Chipset</b>	Processor Graphics Intel® UHD Graphics 630 (i7-8700T, i5-8500T, i3-8100T) Intel® UHD Graphics 610 (Pentium G5400T, Celeron G4900T)
<b>Resolution</b>	Dual HDMI: Max. resolution 4096x2304 @ 30Hz LVDS: Max. resolution 1920x1080 @ 60Hz
<b>Multiple Display</b>	Triple Display(2* HDMI, 1*LVDS)
Audio	
<b>Chipset</b>	Realtek ALC892
<b>Audio Interface</b>	Mic-In, Line-In, Line-Out
Ethernet	
<b>Chipset</b>	1 x Intel® I211AT 1 x Intel® I219LM
<b>Ethernet Interface</b>	10/100/1000 Base-Tx GbE compatible
<b>LAN Port</b>	2 x RJ-45
Mechanical & Environmental	
<b>Power Requirement</b>	+12V
<b>ACPI</b>	Single Power ATX Support S0, S1, S3, S4, S5 ACPI3.0 Compliant
<b>Power Type</b>	AT/ATX
<b>Operating Temp</b>	0°C ~ 60°C (32°F ~ 140°F)
<b>Storage Temp</b>	-40°C ~ 75°C (-40°F ~ 167°F)
<b>Operating Humidity</b>	0% ~ 90% Relative Humidity, Non-condensing



<b>Dimension (L x W)</b>	5.7" x 4" (146mm x 101mm)
<b>Weight</b>	0.44lbs (0.2kg)
<b>Certifications</b>	
<b>Certification Information</b>	CE FCC Class B
<b>Software Support</b>	
<b>OS Information</b>	Win 10 Linux
<b>System Control</b>	
<b>LED Indicator</b>	1 x Power on/off LED on Rear side 1 x Storage Access LED on Rear side

**+ Ordering**

ECM-CFS  
8th Gen Intel® Core™ i7/i5/i3/Celeron® 3.5" Micro Module with Intel® Q370 chipset