

Literature APPLICATION Guide

60mm Universal Stacklight with Sound



KEY FEATURES:

- 1 to 5 Stacks Available
- Colored Transparent Lenses
- 24 Vac/dc or 120 Vac Only
- 12 in Pole or Direct Mount
- CE (24 Vac/dc Models)
- UL & CUL Approved; NEMA 12; IP-52
- Wire Termination
- Preferred 2000 Hz Sound Frequency
- Each Unit Includes 4 Sound Options:
 - Continuous
 - Medium Pulse (5 pps)
 - Slow Double Pulse
 - Continuous Tone for 5 Seconds Followed by a Short Pulse Tone Every 1 Second

SPECIFICATIONS:

Voltage Rating: 24 Vac/dc (20 to 28 Volts) 120 Vac (90 to 120 Volts)	Stack Light Shape: Triangle
Sound Level: 80 to 85 dB Typ @ 1 Meter	Stack Colors: Red; Yellow; Green; Blue; Clear
Sound Frequency: 2000 Hz	Lens Material: Lexan CFR7431
Sound Current: 40 mA max	LED Current: 60 mA or less per Stack
Sound Direction: Omni-directional	Termination: 22 AWG Wires- 48 inches
Operating Temp: -25 to 60 °C	Direct Mount Option: ½" NPT Pipe & Nut
Storage Temp: -25 to 60 °C	Pole Mount Options: 12" Stainless Pole & Bracket 12" Black Electroplated Pole & Bracket
cUL File No.: NKCR8.E478987	NEMA & IP Rating: NEMA 12; IP-52
UL File No.: NKCR2.E478987	
Case Material: ABS FR15U	

Part Number Structure

JTC 028 - RYCBC - C D L

Series: **JTC** = Color Lens 60mm Stacklight

Maximum Voltage:

028 = 20 to 28 Vac/dc; **120** = 90 to 120 Vac Only

Stack Colors:

R = Red; **Y** = Yellow/Amber; **G** = Green; **B** = Blue; **C** = Clear/White

Light Function:

All Models: **C** = Continuous

1 Stack Only: **C** = Continuous; **P** = Slow Pulse; **M** = Med Pulse; **F** = Fast Pulse

Mounting Type:

D = Direct; **S** = Stainless Pole; **E** = Black Electroplated Pole

Sound Loudness (Typical @ 1 Meter):

L = Loud (80 to 85 dB); **M** = Medium (70 to 75 dB)

Physical Height (Above the Mounting Surface)

# Stacks	Direct Mount	12" Pole
1	4.5 in (114 mm)	17.1 in (432 mm)
2	6.0 in (152 mm)	18.1 in (460 mm)
3	7.5 in (191 mm)	20.0 in (508 mm)
4	9.0 in (229 mm)	21.1 in (536 mm)
5	10.5 in (267 mm)	23.0 in (584 mm)

Call 317-612-1000 or Visit www.mspindy.com for More Details