



KIWI330

1.6" SBC with Intel Alder Lake-N® Processor, LPDDR5, eDP, M.2 Key E, 2 USB 3.2 (Type-C), and USB 3.2 (Vertical Type-C)



Features

- Super tiny 1.6-inch embedded board
- Intel Alder Lake-N® processor onboard
- Onboard 4GB LPDDR5 memory
- Onboard 64GB NVMe SSD storage
- Supports M.2 Key E socket
- Supports eDP for display
- Supports operating system: Linux, Windows®

Specifications

Core System

CPU	Intel Alder Lake-N® processor
System Memory	On-board 4GB LPDDR5
Chipset	SoC integrated
BIOS	AMI
Storage	BGA 64GB NVMe
Watchdog Timer	255 levels, 1 to 255 sec
Expansion Interface	1 x M.2 Key E 2230 (USB 2.0, PCIe)
Battery Lithium	Lithium 3V/225 mAh
Power Input	2-pin Phoenix type
Power Requirements	12 VDC/5A

Specifications

Display

Chipset	Intel® UHD Graphics
Memory Size	Shared system memory
Display Interface	1 x eDP

I/O

SATA	N/A
Hardware Monitoring	Detect temperature, voltage, and fan speed
Ethernet	N/A
USB	Horizontal: 1 x USB 3.2 Type-C (2 x USB 3.2 + 2 x USB 2.0 + 5V/3A + DisplayPort) 1 x USB 3.2 Type-C (2 x USB 3.2 + 2 x USB 2.0 + 5V/3A) Vertical: 1 x USB 3.2 Type-C (2 x USB 3.2 + 2 x USB 2.0 + 5V/3A) Internal: 1 x USB 2.0 header (1 x 4-pin wafer)
TPM	N/A

Mechanical and Environmental

Dimensions	72 mm × 56 mm
Board Thickness	1.6 mm
Operating Temperature	0°C to +60°C (+32°F to +140°F)
Relative Humidity	10% to 95% relative humidity, non-condensing

Ordering Information

Standard

KIWI330-N50-S (P/N: E3D0330100)	Intel® processor N50, 4GB LPDDR5, and 64GB NVMe SSD
KIWI330-N50-M5 (P/N: E3D0330103)	Intel® processor N50, 4GB LPDDR5, and 64GB NVMe SSD with MIO335

Optional

MIO334-6COM-S (P/N: E39Q334101)	6-port COM module, 3 DB9 RS-232, and 3 header RS-232
MIO335-2LAN-S (P/N: E39Q335101)	Dual GbE LAN module, 2 RJ-45 GbE LAN, and 2 USB 2.0 Type-A
USB cable (P/N: 594P8802810E)	USB-to-1.25_4-pin housing, L = 150 mm
COM cable (P/N: 59380880250E)	COM-port cable, DB9 - 9 × 1 P, L = 250 mm, P = 1.25
Adapter (P/N: 50966124050E)	Adapter 12V 60W FSP060-DHAN3 with screw



Packing List

1 x KIWI330 or 1 x KIWI330 + 1 x MIO335
1 x KIWI330 cooler
1 x DC wired cable

Block Diagram

